




Reverse Formed Wedge Wire Screen Pipe Specification

When ordering, please specify:

1. Pipe Diameter
2. Slot Size
3. Profile Wire
4. Support Wire
5. Pipe Length



Internal Circumferential Wire with External Axial Support Rods

Technical Parameter

Pipe Diameter		Slot Size		Profile Wire	Support Wire	Max. Length	
inch	mm	inch	mm	type	type	ft.	m
4	101	0.008 - 0.079	0.2 - 2.0	18 TP, 22 TP	18 TP, 22 TP, 24 TP, Q25	9.84	3.00
4 1/2	114	0.008 - 0.079	0.2 - 2.0	18 TP, 22 TP	22 TP, 24 TP, Q25	9.84	3.00
5	127	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, Q25	9.84	3.00
6 5/8	168	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, 34 TP, Q25	9.84	3.00
7	178	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, 34 TP, Q25	9.84	3.00
8 5/8	219	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	22 TP, 24 TP, 34 TP, Q35	9.84	3.00
9 5/8	244	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	22 TP, 24 TP, 34 TP, Q35	9.84	3.00
10 3/4	273	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	24 TP, 34 TP, Q35	9.84	3.00
12 3/4	324	0.008 - 0.098	0.2 - 2.5	28 TP, 34 TP	34 TP, RD45	9.84	3.00
24	610	0.008 - 0.118	0.2 - 3.0	28 TP, 34 TP	34 TP, RD45	9.84	3.00
36	914	0.008 - 0.118	0.2 - 3.0	28 TP, 34 TP	34 TP, RD45	9.84	3.00
60	1524	0.008 - 0.118	0.2 - 3.0	28 TP, 34 TP	34 TP, RD45	9.84	3.00
71	1800	0.008 - 0.118	0.2 - 3.0	28 TP, 34 TP	34 TP, RD45	9.84	3.00