




Standard Wedge Wire Wrapped Screen Pipe Specification

When ordering, please specify:

1. Pipe Diameter
2. Slot Size
3. Profile Wire
4. Support Wire
5. Pipe Length



External Circumferential Wire and Axial Internal Support Rods

Technical Parameter

Pipe Diameter		Slot Size		Profile Wire	Support Wire	Max. Length	
inch	mm	inch	mm	type	type	ft.	m
2 7/8	73	0.008 - 0.059	0.2 - 1.5	10 TP	10 TP, 18 TP, 22 TP, Q25	19.68	3.00
3 1/2	89	0.008 - 0.059	0.2 - 1.5	18 TP, 22 TP	18 TP, 22 TP, 24 TP, Q25	19.68	6.00
4	101	0.008 - 0.079	0.2 - 2.0	18 TP, 22 TP	18 TP, 22 TP, 24 TP, Q25	19.68	6.00
4 1/2	114	0.008 - 0.079	0.2 - 2.0	18 TP, 22 TP	22 TP, 24 TP, Q25	19.68	6.00
5	127	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, Q25	19.68	6.00
6 5/8	168	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, 34 TP, Q25	19.68	6.00
7	178	0.008 - 0.098	0.2 - 2.5	18 TP, 22 TP	22 TP, 24 TP, 34 TP, Q25	19.68	6.00
8 5/8	219	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	22 TP, 24 TP, 34 TP, Q35	39.37	12.00
9 5/8	244	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	22 TP, 24 TP, 34 TP, Q35	39.37	12.00
10 3/4	273	0.008 - 0.098	0.2 - 2.5	22 TP, 28 TP	24 TP, 34 TP, Q35	39.37	12.00
12 3/4	324	0.008 - 0.098	0.2 - 2.5	28 TP, 34 TP	34 TP, FB 325, RD45	39.37	12.00
24	610	0.008 - 0.236	0.2 - 6.0	28 TP, 34 TP	34 TP, FB 325, RD45	19.68	6.00
36	914	0.008 - 0.354	0.2 - 9.0	28 TP, 34 TP	34 TP, FB 310, FB 325, RD45	19.68	6.00
60	1524	0.008 - 0.394	0.2 - 10.0	28 TP, 34 TP	34 TP, FB 310, FB 325, RD45	19.68	6.00