B R O C H U R E

Sand Plant



Sieve Bend Screen for Sand Plant



Objective

The sand is a main part of construction industry, the demand for sand and concrete exceeds the supply in the global market. However, the natural sands have already got fewer. For resources conservation and environment protection, using the manufactured sand rather than natural sand in the concrete is inevitable trend. Thus, it is very important for screening the manufactured sand.

Solution

Sieve bend screen are widely used in sand screening plants, the screen can separates fine sand from the raw materials. For example, sieve bend screen can recover any fine sand particles that were lost during the lignite removal process. This sieve bend separates the lignite from the sand and water which is subsequently sent to a fines recovery sand washing plant.





Idea for	Screen Size	Features & Benefits
Sand plants	 0.3 mm slot 0.4 mm slot 0.5 mm slot 0.75mm slot 	 V type wire, non-clogging Wear and corrosion resistance Low operating costs and great ease of operation Very low installation costs, no maintenance Improves efficiency of vibrating screens immediately downstream

Technical Parameters


When odering, please specify:


- 1. Wedge Wire
- 2. Slot Hole
- **3. Radian** 45°, 60°
- **4. Radius** 1016mm, 2032mm
- 5. Arc Length
- 6. Panel Width





45 Degree x 1016 mm Radius, 800 mm Arc Length





60 degree x 2032 mm Radius, 2130 mm Arc Length

Headquarters

Web Wire Mesh Co.,Ltd. No.12 Weier Rd. EZD Industrial Park Hebei, China

Tel: +86 0318 7568801 Fax: +86 0318 7568802

We b site: www. we bwedgewire. com

Branch

Web Wire Mesh Co.,Ltd.-SJZ NO 2701 CYC Shijiazhuang City Hebei, China Tel: +86 0311 89255081

E-mail: zhao@webwirecloth.com



Anping Web Wire Mesh Co.,Ltd.